

MATERIAL SAFETY DATA SHEET

25-600 -- ADVANTAGE ACRYLIC LATEX SEMIGLOSS Printed: 09/11/07 Revised: 02/08/02

Page

=====

EMERGENCY TELEPHONE: 305-558-7315

Manufacturer:		----- HMIS CODES -----
EVERLASTING COATINGS&PAINTS	Hazard Rating:	Health 1
1701 PENNSYLVANIA AVE, NW	Least --> Greatest	Flammability 0
WASHINGTON, DC 20006	0 --> 4	Reactivity 0
Phone: 301-681-0003		Personal Protection B

SECTION IIA: HAZARDOUS	SECTION I: PRODUCT IDENTIFICATION
------------------------	-----------------------------------

Product Code: 25-600	Product Class: PAINT
Product Name: 25-600 LATEX S/G WHITE	
Chemical Name: ADVANTAGE ACRYLIC LATEX SEMIGLOSS	CAS Number: NA

Ingredient	CAS Number	INGREDIENTS		Vapor LEL
		(To Nearest % 1.00%) by	Vol.	
1. ETHYLENE GLYCOL	107-21-1	by Wt. % 4.00	5.00 NE	Press. 3.2
	NA = Not	Applicable;	= Not	Established

SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS

Ingr. #	-----OSHA PEL's-----		-----ACGIH TLV's-----		OSHA
	ppm	mg/m3	ppm	mg/m3	
1.	50	NE	NE	100.00	100
				100.00	100.00
				NA = Not Applicable;	NE = Not Established

SECTION III: PHYSICAL DATA

Boiling Range (degrees F): 212.00 - 220.00 Pounds per Vapor Gallon: 10.39
Density: LIGHTER THAN AIR Evaporation Rate: SLOWER THAN ETHER
Solubility in Water: S
Appearance: WHITE OR COLORED LIQUID

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:
OSHA: 0 DOT: NA
Flash Point: NA (Method: Na)
UEL: NA

Extinguishing Media: FOAM,C02,DRYCHEMICAL

Unusual Fire and Explosion Hazards

MATERIAL MAY SPLATTER ABOVE 212 DGS.F.SEALED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Special Firefighting Procedures

POLYMER FILM CAN BURN.AVOID BREATHING FUMES, TRACE AMOUNTS OF CARBON DIOXIDE-CARBON MONOXIDE MAY BE RELEASED.COOL CONTAINERS WITH WATER.

MATERIAL SAFETY DATA SHEET

25-600 -- **ADVANTAGE** ACRYLIC LATEX SEMIGLOSS Printed: 09/11/07 Revised: 02/08/02 Page
2

SECTION V: HEALTH HAZARD DATA

Effects of Overexposure
HEADACHE, NAUSEA, AND IRRITATION OF NOSE, THROAT, AND LUNGS.

Medical Conditions Prone to Aggravation by Exposure
NONE KNOWN

Primary Routes of Entry into the Body, and Effects
INHALATION, SKIN, EYES, AND, SWALLOWING.

EMERGENCY FIRST-AID PROCEDURES

EYE AND SKIN CONTACT: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15
MINUTES. CONSULT PHYSICIAN. WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION:
MOVE SUBJECT TO FRESH AIR.

SECTION VI: REACTIVITY DATA

Stability: STABLE Hazardous Polymerization WILL NOT OCCUR.

Hazardous Decomposition Products
CARBON DIOXIDE/CARBON MONOXIDE

Conditions to Avoid
NONE KNOWN

Incompatibilities (Materials to Avoid)
NONE KNOWN

SECTION VII: SPILL OR LEAK PROCEDURES; WASTE DISPOSAL

Steps to be taken if Material is Leaked or Spilled
AVOID CONTACT. SOAK UP WITH ABSORBENT MATERIAL. KEEP SPILLS OUT OF MUNICIPAL
SEWERS AND OPEN BODIES OF WATER.

Waste Disposal Methods
DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION VIII: SAFE HANDLING AND USE INFORMATION

Respiratory Protection
DUST AND MIST MASK SUCH AS TC-21C-141 OR TC-21C-183 FOR PARTICULATE DUST PRO-
TECTION.

Ventilation
MECHANICAL EXHAUST MAY BE REQUIRED IN CONFINED AREAS.

Protective Gloves
RUBBER GLOVES REQUIRED FOR PROLONGED CONTACT.

Eye Protection
GOGGLES CAPABLE OF PROTECTION AGAINST SPLASH OR SPRAY (ANZI Z87 OR EQUAL).

Page 2

ADVANTAGE ACRYLIC LATEX
SEMIGLOSS

Revision Date: 02/08/02

MATERIAL SAFETY DATA SHEET

25-600 - **ADVANTAGE** ACRYLIC LATEX SEMIGLOSS Printed: 09/11/07 Revised: 02/08/02
Page

Other Protective Equipment
USUALLY NOT REQUIRED.

Hygienic Practices
NORMAL HYGIENIC PRACTICES SHOULD BE FOLLOWED.

SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing
KEEP IN AREA WITH TEMPERATURES NOT BELOW 50 DGS.F.OR ABOVE 100 DGS.F.KEEP
CONTAINERS LABELED. KEEP OUT OF THE REACH OF CHILDREN.

Other Precautions
NONE KNOWN.

Disclaimer:THIS INFORMATION IS BASED ON TECHNICAL DATA BELIEVED TO BE ACCURATE AND
RELIABLE, BUT IS FURNISHED WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES.

END OF MSDS

24 Hour Emergency Contact Information:

1-(800)-255-3924 U.S.A. & Canada
Outside the U.S.A.
Country Code can originating from then **+ 01-813-248-0585**