

MATERIAL SAFETY DATA SHEET

11-600 -- ADVANTAGE SATIN WHITE Printed: 09/11/07 Revised: 02/07/02 Page 1

Hazard Rating: Health 1

----- HMIS CODES -----

Manufacturer:

EMERGENCY TELEPHONE: 305-558-7315

EVERLASTING COATINGS&PAINTS
1701 PENNSYLVANIA AVE, NW
WASHINGTON, DC 20006
Phone: 301-681-0003

Least --> Greatest Flammability 0
0 --> 4 Reactivity 0
Personal Protection B

SECTION I: PRODUCT IDENTIFICATION

Product Code: 11-600
PAINT

Product Class:

Product Name: 11-600 ADVANTAGE SATIN WHITE

Chemical Name: ADVANTAGE SATIN WHITE CAS Number: NA

SECTION IIA: HAZARDOUS INGREDIENTS

Table with 5 columns: Ingredient, CAS Number, (To Nearest % by Wt. %3.00), % 1.00% by Vol., Vapor LEL Press. 3.2. Row 1: 1. ETHYLENE GLYCOL, 107-21-1, Applicable; 4.00 NE, = Not Established.

SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS

Table with 7 columns: Ingr. #, ppm OSHA, mg/m3 TWA, ppm TWA, mg/m3 STEL, ppm STEL, mg/m3 OSHA. Row 1: 1, 50, NE, NE, 100.00, 100, 100.00.

SECTION III: PHYSICAL DATA

Boiling Range (degrees F): 212.00 - 220.00 Pounds per Gallon: 10.86
Vapor Density: LIGHTER THAN AIR Evaporation Rate: SLOWER THAN
ETHER
Solubility in Water:
S Appearance: WHITE
LIQUID

SECTION IV: FIRE AND EXPLOSION HAZARD

DATA Flammability Classification:
OSHA: 0 DOT: NA
Flash Point: NA (Method: Na)
UEL: NA

Extinguishing Media: FOAM, C02, DRYCHEMICAL

Unusual Fire and Explosion Hazards

MATERIAL MAY SPLATTER ABOVE 212 DGS.F. SEALED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Special Firefighting Procedures

POLYMER FILM CAN BURN.AVOID BREATHING FUMES, TRACE AMOUNTS OF CARBON DIOXIDECARBON MONOXIDE MAY BE RELEASED.COOL CONTAINERS WITH WATER.

MATERIAL SAFETY DATA SHEET

11-600 -- **ADVANTAGE** SATIN WHITE Printed: 09/11/07 Revised: 02/07/02 Page 2

SECTION V: HEALTH HAZARD DATA

Effects of Overexposure
HEADACHE, NAUSEA, AND IRRITATION OF NOSE, THROAT, AND LUNGS.

Medical Conditions Prone to Aggravation by
Exposure NONE KNOWN

Primary Routes of Entry into the Body, and
Effects INHALATION, SKIN, EYES, AND,
SWALLOWING.

EMERGENCY FIRST-AID PROCEDURES

EYE AND SKIN CONTACT: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST
15 MINUTES. CONSULT PHYSICIAN. WASH AFFECTED AREA WITH SOAP AND WATER.

INHALATION:
MOVE SUBJECT TO FRESH AIR.

**SECTION VI: REACTIVITY
DATA**

Stability: STABLE Hazardous Polymerization WILL NOT OCCUR.

Hazardous Decomposition
Products CARBON
DIOXIDE/CARBON MONOXIDE

Conditions to
Avoid NONE
KNOWN

Incompatibilities (Materials to
Avoid) NONE KNOWN

**SECTION VII: SPILL OR LEAK PROCEDURES; WASTE
DISPOSAL** Steps to be taken if Material is Leaked or Spilled
AVOID CONTACT. SOAK UP WITH ABSORBENT MATERIAL. KEEP SPILLS OUT OF
MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

Waste Disposal Methods
DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

**SECTION VIII: SAFE HANDLING AND USE
INFORMATION** Respiratory Protection
DUST AND MIST MASK SUCH AS TC-21C-141 OR TC-21C-183 FOR PARTICULATE DUST
PROTECTION.

Ventilation
MECHANICAL EXHAUST MAY BE REQUIRED IN CONFINED AREAS.

Protective Gloves
RUBBER GLOVES REQUIRED FOR PROLONGED CONTACT.

Eye Protection
GOGGLES CAPABLE OF PROTECTION AGAINST SPLASH OR SPRAY (ANZI Z87 OR EQUAL).

MATERIAL SAFETY DATA SHEET

11-600 -- **ADVANTAGE** SATIN WHITE Printed: 09/11/07 Revised: 02/07/02 Page 3

Other Protective Equipment USUALLY
NOT REQUIRED.

Hygienic Practices
NORMAL HYGIENIC PRACTICES SHOULD BE FOLLOWED.

SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing
KEEP IN AREA WITH TEMPERATURES NOT BELOW 50 DGS.F.OR ABOVE 100 DGS.F.KEEP CONTAINERS
LABELED. KEEP OUT OF THE REACH OF CHILDREN.

Other Precautions NONE
KNOWN.

Disclaimer: THIS INFORMATION IS BASED ON TECHNICAL DATA BELIEVED TO BE ACCURATE AND
RELIABLE, BUT IS FURNISHED WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES.

END OF MSDS

24 Hour Emergency Contact Information:

1-(800)-255-3924 U.S.A. & Canada Outside the U.S.A.
Country Code can originating from then **+ 01-813-248-0585**